






## Fresa ad inserti a finire per macchine bordatrici

*Jointing cutter with knives for edge-banding machines*




### SIMMETRICA


ØD	S	Z	Tipo	Foro	Codice
80	43	3x4	S	30+2CH	<b>AS40.S.080.043</b>
80	65	3x6	S	30+2CH	<b>AS40.S.080.065</b>
100	43	3x4	S	30+2CH	<b>AS40.S.100.043</b>
100	65	3x6	S	30+2CH	<b>AS40.S.100.065</b>
125	43	3x4	S	30+2CH	<b>AS40.S.125.043</b>
125	65	3x6	S	30+2CH	<b>AS40.S.125.065</b>

### ASIMMETRICA

100	43	2x4	AS	20+2CH	<b>AS40.A.100.043.2.R/L</b>
100	54	2x5	AS	30+2CH	<b>AS40.A.100.054.2.R/L</b>
100	65	2x6	AS	30+2CH	<b>AS40.A.100.065.2.R/L</b>
85	43	3x4	AS	30+2CH	<b>AS40.A.085.043.3.R/L</b>
100	32	3x3	AS	30+2CH	<b>AS40.A.100.032.3.R/L</b>
100	43	3x4	AS	30+2CH	<b>AS40.A.100.043.3.R/L</b>
100	54	3x5	AS	30+2CH	<b>AS40.A.100.054.3.R/L</b>
100	65	3x6	AS	30+2CH	<b>AS40.A.100.065.3.R/L</b>
100	85	3x8	AS	30+2CH	<b>AS40.A.100.085.3.R/L</b>
100	105	3x10	AS	30+2CH	<b>AS40.A.100.105.3.R/L</b>
125	32	3x3	AS	30+2CH	<b>AS40.A.125.032.3.R/L</b>
125	43	3x4	AS	30+2CH	<b>AS40.A.125.043.3.R/L</b>
125	54	3x5	AS	30+2CH	<b>AS40.A.125.054.3.R/L</b>
125	65	3x6	AS	30+2CH	<b>AS40.A.125.065.3.R/L</b>
125	85	3x8	AS	30+2CH	<b>AS40.A.125.085.3.R/L</b>
125	105	3x10	AS	30+2CH	<b>AS40.A.125.105.3.R/L</b>



Tipo AS = asimmetrico  
Type AS = asymmetric



Tipo S = simmetrico  
Type S = symmetric

### Caratteristiche

Fresa per spianare a spessore costante per macchine bordatrici. Altezza diamante 3 mm.

### Characteristics

Cutterhead with constant thickness for edge-banding machines. Diamond height 3 mm.